



Description

100 mm high steel wire mesh tray with surface protection, or stainless steel AISI 304 or 316L, with rounded safety edge for the support and management of cables. The Rejiband cable tray is made up of a mesh of electrowelded rods that provide high strength and elasticity. The ease of installation, thanks to its flexibility saves on material and labour costs. Manufactured according to international standard IEC 61537. Its wide variety of sizes and Protection Systems facilitates the most appropriate choice according to the needs of each installation.

Advantages

High resistance, flexibility and adaptable to each project providing a saving of more than 30% in the installation.

Rounded safety edge that prevents damage to the cables and harm to the installer.

N Mark of Aenor, UL Certificate, Certificate IECC CB according to IEC 61537.

E90 fire resistance (90 minutes, 1000°C) according to DIN 4102-12.

Flange height 100 mm and available in widths of 100, 150, 200, 300, 400, 500 and 600 mm with a wide range of accessories.

Applications

Support, management and distribution of cables in Electrical and/or telecommunications installations in: Civil Works, Tunnels, Car Parks, Public Buildings, Shopping Centres, Data Processing Centres, Infrastructures, Airports, Underground and Railway. Tertiary sector and industrial applications: Naval, Petrochemical, Textile, Chemical and Food. Indoor applications in the dry or in exterior atmospheres with wet environments according to the various finishes.

Solutions



INDUSTRIA ALIMENTARIA INDUSTRIA QUIMICA FARMACEUTICA INDUSTRIA PETROQUÍMICA ENERGÍA FOTOVOLTAICA CENTROS DE DATOS EDIFICACIÓN. TERCIARIO



TUNELES. INFRAESTRUCTURAS RESISTENCIA AL FUEGO



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



Main technical characteristics

100	100, 150, 200, 300, 400, 450, 500, 600	3	20 J	-50 / 150 °C	ETIM EC000853
-----	--	---	------	--------------	------------------

Product data

Class	Ref	kg/u	W	M	mm ²	⚡
EZ Class 3	100 60213100	1.080	12	Steel with surface coating	7742	E90 (90 min. 1000°C)
EZ Class 3	150 60213150	1.152	6	Steel with surface coating	12352	E90 (90 min. 1000°C)
EZ Class 3	200 60213200	1.381	6	Steel with surface coating	16596	E90 (90 min. 1000°C)
EZ Class 3	300 60213300	2.038	6	Steel with surface coating	25716	E90 (90 min. 1000°C)
EZ Class 3	400 60213400	2.405	6	Steel with surface coating	34836	E90 (90 min. 1000°C)
EZ Class 3	450 60213450	2.468	6	Steel with surface coating	39396	E90 (90 min. 1000°C)
EZ Class 3	500 60213500	2.771	6	Steel with surface coating	43956	A1 No combustible
EZ Class 3	600 60213600	3.138	6	Steel with surface coating	53076	A1 No combustible
GC Class 7	100 60233100	1.061	12	Steel with surface coating	7742	E90 (90 min. 1000°C)
GC Class 7	150 60233150	1.232	6	Steel with surface coating	12352	E90 (90 min. 1000°C)
GC Class 7	200 60233200	1.532	6	Steel with surface coating	16596	E90 (90 min. 1000°C)
GC Class 7	300 60233300	2.342	6	Steel with surface coating	25716	E90 (90 min. 1000°C)
GC Class 7	400 60233400	2.833	6	Steel with surface coating	34836	E90 (90 min. 1000°C)
GC Class 7	450 60233450	2.923	6	Steel with surface coating	39396	A1 No combustible
GC Class 7	500 60233500	3.353	6	Steel with surface coating	43956	A1 No combustible
GC Class 7	600 60233600	3.883	6	Steel with surface coating	53076	A1 No combustible
INOX Class 9C	100 60253100	1.321	12	Stainless steel AISI 304	7582	E90 (90 min. 1000°C)
INOX Class 9C	150 60253150	1.358	6	Stainless steel AISI 304	12162	E90 (90 min. 1000°C)
INOX Class 9C	200 60253200	1.661	6	Stainless steel AISI 304	16742	E90 (90 min. 1000°C)
INOX Class 9C	300 60253300	2.028	6	Stainless steel AISI 304	25902	E90 (90 min. 1000°C)
INOX Class 9C	400 60253400	2.385	6	Stainless steel AISI 304	35062	E90 (90 min. 1000°C)
INOX Class 9C	500 60253500	2.751	6	Stainless steel AISI 304	44222	A1 No combustible
INOX Class 9C	600 60253600	3.118	6	Stainless steel AISI 304	53382	A1 No combustible
INOX Class 9D	100 60263100	1.330	12	Acero inoxidable AISI 316L	7582	E90 (90 min. 1000°C)
INOX Class 9D	150 60263150	1.372	6	Acero inoxidable AISI 316L	12162	E90 (90 min. 1000°C)
INOX Class 9D	200 60263200	1.661	6	Acero inoxidable AISI 316L	16742	E90 (90 min. 1000°C)
INOX Class 9D	300 60263300	2.028	6	Acero inoxidable AISI 316L	25902	E90 (90 min. 1000°C)
INOX Class 9D	400 60263400	2.385	6	Acero inoxidable AISI 316L	35062	E90 (90 min. 1000°C)
INOX Class 9D	500 60263500	2.751	6	Acero inoxidable AISI 316L	44222	A1 No combustible
INOX Class 9D	600 60263600	3.118	6	Acero inoxidable AISI 316L	53382	A1 No combustible
BK8 Class 8	100 60283100	1.080	12	Steel with surface coating	7742	E90 (90 min. 1000°C)
BK8 Class 8	150 60283150	1.138	6	Steel with surface coating	12352	E90 (90 min. 1000°C)
BK8 Class 8	200 60283200	1.381	6	Steel with surface coating	16596	E90 (90 min. 1000°C)
BK8 Class 8	300 60283300	2.038	6	Steel with surface coating	25716	E90 (90 min. 1000°C)
BK8 Class 8	400 60283400	2.405	6	Steel with surface coating	34836	E90 (90 min. 1000°C)
BK8 Class 8	450 60283450	2.468	6	Steel with surface coating	39396	A1 No combustible



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



Ⓢ	Class	Ⓜ	REF	kg/u	Ⓜ	Ⓜ	mm ²	Ⓜ
BK8	Class 8	500	60283500	2.771	6	Steel with surface coating	43956	A1 No combustible
BK8	Class 8	600	60283600	3.138	6	Steel with surface coating	53076	A1 No combustible

Ⓢ Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Ⓜ Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic



Load diagrams

□

Product applications

