

Rejiband SAFECu Wire mesh tray

1/3



Description

Rejiband® SAFECu wire mesh tray for cable support and management. The Rejiband® SAFECu cable tray is composed of electrowelded carbon steel rods. Intended for indoor environments classified as corrosivity category C1/C2 according to the ISO 9223 standard, it is the hygienic-sanitary solution for all types of spaces where there is public attendance, thanks to its CU, antimicrobial and COVID-free protection system.

Advantages

Self-extinguishing flame retardant PVC outer sheath.

Suitable for the support of wire mesh trays or other items with loads between 35 and 90 kg according to the reference.

Surface shaped with rounded rods avoiding edges and reducing contact surface

CE conformity in accordance to the low voltage directive 2014 /35 /UE and the international product standard IEC 61537

SAFECu Protection system, copper-plated treatment, which confers hygienic properties by eliminating bacteria, viruses and fungi

Applications










Solutions



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



Main technical characteristics						
 CU	 Class 1	 60, 100	 100, 150, 200, 300, 450, 600	 2	 Steel with surface coating	 20 J
			ETIM			
 -50 / 150 °C	 A1 No combustible					

Product data						
		mm²	Ref	kg/u		mm²
60	100	4	82003241	0.793	16	4442
60	150	4	82003242	0.847	16	6976
60	200	4	82003243	1.094	12	9586
60	300	4.5	82003244	1.702	8	14420
60	450	4.5	82003245	2.134	4	22100
60	600	4.5	82003247	2.810	4	29780
100	100	4	82003248	1.074	8	7742
100	150	4	82003249	1.158	4	12352
100	200	4	82003250	1.388	4	16596
100	300	4.5	82003251	2.045	4	25716
100	450	4.5	82003252	2.472	4	39396
100	600	4.5	82003254	3.146	4	53076

Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester

Rejiband SAFECu Wire mesh tray

TPV - Thermoplastic



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

