

Description

Steel wire mesh tray with heights of 60 and 100 mm, surface protection and safety edge. Used in industrial installations for the support and management of electric cables in false ceilings, confined spaces and on walls. The ease of installation is thanks to the Click quick connect system that requires no fixings for supports and accessories. It requires no additional support and is attached to the ceiling and walls by using just the Rejitech fixing. It has an open structure that allows the lateral introduction of the cables therefore reducing the installation time. Available in different sizes and Protection Systems. It is supplied in 3 m lengths. Manufacturing according to international standard IEC 61537.

Advantages

Direct fixing to the ceiling without additional support by using just the Rejitech Fastener.

Cables are kept tidy and with maximum ventilation.

Installation in false ceilings or confined spaces.

Quick installation by just one person.

It installs quickly without the need for joints or bends.

Applications

Suitable for the management and distribution of cables in electrical and/or telecommunications in industrial installations, Civil Works and Infrastructures, tunnels and inspection galleries. It is mainly used for installations in false ceilings due to its height of 60 mm allowing it to be accommodated in reduced spaces.

Solutions



INDUSTRIA QUIMICA FARMACEUTICA



INDUSTRIA PETROQUÍMICA



ENERGÍA



FOTOVOLTAICA



CENTROS DE DATOS



EDIFICACIÓN. TERCIARIO



TUNELES. INFRAESTRUCTURAS



SECTOR FERROVIARIO



RESISTENCIA AL FUEGO










www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



Main technical characteristics

 60, 100	 60, 100, 150, 200	 mm² 4	 Steel with surface coating	 20 J	 -50 / 150 °C	 A1 No combustible
ETIM EC000853						

Product data

§	61537				Ref	kg/u		mm²
EZ	Class 3	60	60	3	60613206	0.666	24	676
EZ	Class 3	100	60	3	60613306	0.824	24	1975
EZ	Class 3	100	100	3	60613310	0.970	12	3787
EZ	Class 3	100	150	3	60613315	1.032	6	6052
EZ	Class 3	100	200	3	60613320	1.285	6	8317
BC	Class 5	100	60	3	60623306	0.824	24	1975
BC	Class 5	100	150	3	60623315	1.032	6	6052
BK8	Class 8	60	60	3	60683206	0.666	24	676
BK8	Class 8	100	60	3	60683306	0.824	24	1975
BK8	Class 8	100	100	3	60683310	0.970	12	3787
BK8	Class 8	100	150	3	60683315	1.032	6	6052
BK8	Class 8	100	200	3	60683320	1.285	6	8317
CU	Class 1	60	60	2	82003264	0.666	16	676
CU	Class 1	100	60	2	82003265	0.824	16	1975
CU	Class 1	100	100	2	82003266	0.970	8	3787
CU	Class 1	100	150	2	82003267	1.031	4	6052
CU	Class 1	100	200	2	82003268	1.284	4	8317

§ Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Ⓜ Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

