


RLH750 Halogen Free Conduit



Description

RLH rigid pipe for the protection of electrical cables in building applications. Manufactured in halogen-free thermoplastic material (PC + ABS) with a protection rating of IP44, compression strength of 750 N and impact resistance of 6 J. Available in grey (RAL 7035), in a wide variety of sizes.

Advantages

It is produced in 3 m lengths for greater convenience of transport and handling.

Very good performance against impact and compression.

Quick assembly via plug-in connection between conduits and fittings.

CE conformity with directive 2014/35 and standard EN IEC 61386-21.

High security, halogen free material UNE/EN 60754-2 y UNE/EN 60754-1. Reduced smoke opacity and toxicity in the event of a fire. Flame retardant.

Halogen-free according to EN 50642 /EN IEC 61335

Applications

Suitable for the protection of electrical cables in building, tertiary and industrial applications with high safety requirements. Premises of public attendance.

Solutions



SERVICE AND RETAIL



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



RLH750 Halogen Free Conduit

2/2

Main technical characteristics

COLOUR Grey RAL 7035	DN NW16, NW20, NW25, NW32, NW40, NW50, NW63	Polycarbonate + ABS	3432	750 N	6 J
IP44	-15 / 90 °C	Flame retardant	ETIM 10 EC001174		

Product data

DN	Ø _{int}	Ø _{ext}	Ref	kg/u	kg
NW16	13.3	16	13006116	0,074	57
NW20	17.2	20	13006120	0,098	57
NW25	22.2	25	13006125	0,125	57
NW32	29	32	13006132	0,173	30
NW40	36.6	40	13006140	0,246	30
NW50	46.4	50	13006150	0,329	15
NW63	58.6	63	13006163	0,507	15

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

