
RLH fFemale Coupler IP65 (Ref: 81000073)





Description

Fitting with female internal thread for coupling fittings with external thread in the connection of rigid halogen-free RLH or rigid RPVC conduits with flexible TFA and TM-PVC conduits. for DN32 mm, M32, M32. Made of halogen-free thermoplastic (PC+ABS) with an IP65 protection rating. Available in light grey (RAL 7035).

Advantages

High level of tightness and IP65 protection.

CE conformity to the 2014/35 directive and the IEC 61386 standard.

For connection of rigid conduits and flexible conduits.

Quick assembly via plug-in connection for rigid conduits and inside threaded on the other side for flexible conduits

Applications

Suitable for halogen-free and PVC rigid and flexible conduits in buildings, service and industrial applications with high safety requirements especially public places.

Solutions

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

RLH fFemale Coupler IP65 (Ref: 81000073)

Product data

ETIM 10	EC000939
Huella de CO2. GWP A1-A3 (kg CO2 eq.)	
Colour	Grey RAL 7035
DN	NW32
M/PG	M32
G (mm)	15
L (mm)	48.5
kg/u	0,012

u	10
Material	Polycarbonate + ABS
IP	IP54
Working temperature range (°C)	-15 / 90 ºC
Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA

Ⓢ Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Ⓜ Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."