


RLH fFemale Coupler IP65 (Ref: 81000073)

1/2



Description

Fitting with female internal thread for coupling fittings with external thread in the connection of rigid halogen-free RLH or rigid RPVC conduits with flexible TFA and TM-PVC conduits. for DN32 mm, M32, M32. Made of halogen-free thermoplastic (PC+ABS) with an IP65 protection rating. Available in light grey (RAL 7035).

Advantages

High level of tightness and IP65 protection.

CE conformity to the 2014/35 directive and the IEC 61386 standard.

For connection of rigid conduits and flexible conduits.

Quick assembly via plug-in connection for rigid conduits and inside threaded on the other side for flexible conduits

Applications

Suitable for halogen-free and PVC rigid and flexible conduits in buildings, service and industrial applications with high safety requirements especially public places.

Solutions



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



RLH fFemale Coupler IP65 (Ref: 81000073)

2/2

Product data

ETIM 10	EC000939	u	10
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		Material	Polycarbonate + ABS
Colour	Grey RAL 7035	IP	IP54
DN	NW32	Working temperature range (°C)	-15 / 90 °C
M/PG	M32	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA
G (mm)	15		
L (mm)	48,5		
kg/u	0,012		

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic



www.pemsa-rejiband.com



Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."