


**RLH fFemale Coupler IP65** ( Ref: 81000076 )



**Description**

Fitting with female internal thread for coupling fittings with external thread in the connection of rigid halogen-free RLH or rigid RPVC conduits with flexible TFA and TM-PVC conduits. for DN63 mm, M63, M63. Made of halogen-free thermoplastic (PC+ABS) with an IP65 protection rating. Available in light grey (RAL 7035).

**Advantages**

High level of tightness and IP65 protection.

CE conformity to the 2014/35 directive and the IEC 61386 standard.

For connection of rigid conduits and flexible conduits.

Quick assembly via plug-in connection for rigid conduits and inside threaded on the other side for flexible conduits

**Applications**

Suitable for halogen-free and PVC rigid and flexible conduits in buildings, service and industrial applications with high safety requirements especially public places.

**Solutions**



# RLH fFemale Coupler IP65 ( Ref: 81000076 )

2/2

## Product data

|                                       |               |                                |                                              |
|---------------------------------------|---------------|--------------------------------|----------------------------------------------|
| ETIM 10                               | EC000939      | u                              | 5                                            |
| Huella de CO2. GWP A1-A3 (kg CO2 eq.) |               | Material                       | Polycarbonate + ABS                          |
| Colour                                | Grey RAL 7035 | IP                             | IP54                                         |
| DN                                    | NW63          | Working temperature range (°C) | -15 / 90 °C                                  |
| M/PG                                  | M63           | Fire resistance                | LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA |
| G (mm)                                | 15            |                                |                                              |
| L (mm)                                | 68,5          |                                |                                              |
| kg/u                                  | 0,030         |                                |                                              |

## Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

## Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic



[www.pemsa-rejiband.com](http://www.pemsa-rejiband.com)

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

