

RLH IP65 Combined Coupler Kit



Description

Coupler kit for connecting rigid halogen-free RLH or rigid RPVC conduits with TFA and TM-PVC flexible conduits. Made of thermoplastic (PC+ABS) + halogen-free polyamide with an IP65 protection rating. Available in light grey (RAL 7035).

Advantages

High security, halogen free material UNE/EN 60754-2 y UNE/EN 60754-1. Reduced smoke opacity and toxicity in the event of a fire. Flame retardant.

Quick assembly via plug-in connection between conduits and fittings.

Optimal for connecting RLH and RPVC rigid conduits with TFA, TM-PVC flexible conduits

CE conformity to the 2014/35 directive and the IEC 61386 standard.

Applications

Suitable for joining rigid halogen-free and PVC conduits in buildings, service and industrial applications with high safety requirements especially public places.

Solutions



Main technical characteristics

 Colour	Grey RAL 7035	 DN	NW16, NW20, NW25, NW32, NW40, NW50, NW63	 POLIAMIDA 6,POLICARBONATO + ABS	 IP65
 -15 / 90 °C	 LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA	ETIM 10	EC000939		

Product data

DN	DN2	L _{mm}	Ref	kg/u	
NW16	NW 9	69.9	82003200	0,013	5
NW20	NW11	79.9	82003201	0,018	5
NW20	NW13	77.9	82003202	0,018	5
NW25	NW16	85.4	82003203	0,025	5
NW32	NW21	95.4	82003204	0,034	3
NW40	NW29	104.4	82003205	0,048	3
NW50	NW36	118.9	82003206	0,066	2
NW63	NW48	132.4	82003207	0,094	2

 Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

 Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic

RLH IP65 Combined Coupler Kit

Product applications

