

RLH IP65 Combined Coupler Kit (Ref: 82003204)

1/3



Description

Coupler kit for connecting rigid halogen-free RLH or rigid RPVC conduits with TFA and TM-PVC flexible conduits. for DN32 mm. Made of thermoplastic (PC+ABS) + halogen-free polyamide with an IP65 protection rating. Available in light grey (RAL 7035).

Advantages

High security, halogen free material UNE/EN 60754-2 y UNE/EN 60754-1. Reduced smoke opacity and toxicity in the event of a fire. Flame retardant.

CE conformity to the 2014/35 directive and the IEC 61386 standard.

Quick assembly via plug-in connection between conduits and fittings.

Optimal for connecting RLH and RPVC rigid conduits with TFA, TM-PVC flexible conduits

Applications

Suitable for joining rigid halogen-free and PVC conduits in buildings, service and industrial applications with high safety requirements especially public places.

Solutions



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

RLH IP65 Combined Coupler Kit (Ref: 82003204)

Product data			
ETIM 10		EC000939	
Huella de CO2. GWP A1-A3 (kg CO2 eq.)			
Colour		Grey RAL 7035	
DN		NW32	
DN2		NW21	
L (mm)		95.4	
kg/u		0,034	
u		3	
Material		POLIAMIDA 6,POLICARBONATO + ABS	
IP		IP65	
Working temperature range (°C)		-15 / 90 °C	
Fire resistance		LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA	

Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester
TPV - Thermoplastic



RLH IP65 Combined Coupler Kit (Ref: 82003204)

Product applications

□

