
PLASTIC 7035 System

19/11/2026

Conduit RPVC750 (Ref: 13060125)





Description

RPVC rigid conduit for the protection of electrical cables in building applications. Made of plastic material (PVC) with an IP44 protection index, compression resistance of 750 N and impact stregth of 2 J. Available in grey (RAL 7035), in a wide variety of sizes.

Advantages

CE conformity to the 2014/35 directive and the EN IEC 61386 standard.

Quick assembly via plug-in connection between conduits and fittings.

No flame propagation.

It is produced in 3 m lengths for greater convenience of transport and handling.

Speed system that allows the fast introduction and manipulation of cables due to the internal grooves in the conduit.

Applications

Suitable for the protection of electrical wiring in building applications, tertiary sector and industry.

Solutions

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

Conduit RPVC750 (Ref: 13060125)

Product data

ETIM 10	EC001174	**Cod. IEC.61386**	3321
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		**Compression strength (N)**	750 N
Colour	Grey RAL 7035	**Impact Strength (J)**	2 J
DN	NW25	**IP**	IP44
Ø d1 (mm)	22.2	**Working temperature range (°C)**	-5 / 60 °C
Ø d2 (mm)	25	**Fire resistance**	Flame retardant
kg/u	0,198		
u	57		
Material	PVC		

Ⓢ Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Ⓜ Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."