RPVC 90° Bend



Description

90° PVC bend in grey (RAL 7035) with an IP44 index of protection for RPVC rigid conduits. Accessory is used for the assembly of PVC conduits with a push fit connection to the conduit, creating an angle of 90°. Opening for access to cables.

Advantages

For connection of rigid RPVC conduits.

Protection index EN 60529: IP44.

Quick assembly via plug-in connection for conduits and accessories. It allows opening to access and manipulate the cables.

CE conformity to the 2014/35 directive and the IEC 61386 standard.

Made of PVC, not flame retardant.

Applications

Suitable for rigid PVC conduits in building, tertiary and industrial applications.

Solutions

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

RPVC 90° Bend

Main technical characteristics

Colour	DN					ETIM
Grey RAL 7035	NW16, NW20, NW25, NW32	PVC	IP44	-5 / 60 °C	Flame retardant	EC000936

Product data

DN		$L_{(mm)}$	Ref	kg/u	
NW16	16.5	42	55073016	0.007	25
NW20	20.5	50	55073020	0.010	25
NW25	25.5	60	55073025	0.015	25
NW32	30.5	72	55073032	0.023	15

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."