

90° RPVC Bend (Ref: 55017020)

1/2



Description

90° bend in grey colour PVC (RAL 7035) with an index of protection IP44 for RPVC rigid conduits. Accessory is used for the assembly of PVC conduits by a push fit connection, creating a 90° bend.

Advantages

CE conformity to the 2014/35 directive and the EN IEC 61386 standard.

Made of PVC, not flame retardant.

Protection index EN 60529: IP44.

Quick assembly via plug-in connection between conduits and fittings.

For connection of rigid RPVC conduits.

Applications

Suitable for rigid PVC conduits in building, tertiary and industrial applications.

Solutions



Product data

ETIM 10	EC000936	u	25
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		Material	PVC
Colour	Grey RAL 7035	IP	IP44
DN	NW20	Working temperature range (°C)	-5 / 60 °C
Ø d2 (mm)	23	Fire resistance	Flame retardant
L (mm)	90		
kg/u	0,013		

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

