RPVC Tee



Description

Tee in grey colour PVC (RAL 7035) with an IP44 protection rating for RPVC rigid conduits. Accessory used for the assembly of PVC conduits by means of a push fit connection to the conduit, creating a two-way branch. With removable opening.

Advantages

For connection of rigid RPVC conduits.

Protection index EN 60529: IP44.

Quick assembly via plug-in connection for conduits and accessories. It allows opening to access and manipulate the cables.

CE conformity to the 2014/35 directive and the EN IEC 61386 standard.

Made of PVC, not flame retardant.

Applications

Suitable for rigid PVC conduits in building, tertiary and industrial applications.

Solutions

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

RPVC Tee

Main technical characteristics

Colour Grey RAL 7035	DN NW16, NW20, NW25, NW32	PVC	IP44	-5 / 60 °C	Flame retardant	ETIM 10 EC002922

Product data

DN		$L_{(mm)}$	$A_{(mm)}$	REF	kg/u	
NW16	16.5	64	42	55083016	0,010	25
NW20	20.5	76	50	55083020	0,015	25
NW25	25.5	91	60	55083025	0,022	25
NW32	30.5	108	72	55083032	0,033	15

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."