



Description

PVC coupler in grey colour (RAL 7035) with an IP44 protection index for joining RPVC rigid conduits. Assembly by push fit connection to the conduit. Available in different diameters.

Advantages

CE conformity to the 2014/35 directive and the EN IEC 61386 standard.

Made of PVC, not flame retardant.

Protection index EN 60529: IP44.

Quick assembly via plug-in connection between conduits and fittings.

For connection of rigid RPVC conduits.

Applications

Suitable for the joining of rigid PVC conduits in building, tertiary and industrial applications.

Solutions



Product data

ETIM 10	EC000939	Material	PVC
Huella de CO2. GWP A1-A3 (kg CO2 eq.)	2,909	IP	IP44
Colour	Grey RAL 7035	Working temperature range (°C)	-5 / 60 °C
DN	NW32	Fire resistance	Flame retardant
L (mm)	67		
kg/u	0,014		
u	10		

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic