

Coupler Boxes RPVC

1/2



Description

Grey PVC threaded connector (RAL 7035) for the coupling and connection of RPVC rigid conduit to termination or branch boxes in the protection of electrical cables. IP44 protection index. Plug-in connection system and threaded on the other end.

Advantages

For connection of RPVC rigid conduits to boxes.

Protection index EN 60529: IP44.

Quick assembly via plug-in connection between conduits and fittings.

CE conformity to the 2014/35 directive and the IEC 61386 standard.

Made of PVC, not flame retardant.

Applications

Suitable for rigid and corrugated halogen free conduits in building, tertiary and industrial applications with high safety requirements. Premises of public attendance.

Solutions



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



Coupler Boxes RPVC

Main technical characteristics

Colour Grey RAL 7035	DN NW16, NW20, NW25, NW32, NW40, NW50, NW63	⌘ M16, M20, M25, M32, M40, M50, M63	⌘ 15	Ⓜ PVC
IP54	⚡ -5 / 60 °C	⚡ Flame retardant	ETIM 10 EC000939	

Product data

DN	⌘	L _{mm}	Ref	kg/u	Ⓜ
NW16	M16	34.5	55043016	0,004	19
NW20	M20	38.5	55043020	0,005	19
NW25	M25	43.5	55043025	0,008	19
NW32	M32	48.5	55043032	0,010	10
NW40	M40	50.5	55043040	0,013	10
NW50	M50	60.5	55043050	0,020	5
NW63	M63	68.5	55043063	0,028	5

Ⓢ Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Ⓜ Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."