


Conduit Gland Bracket (Ref: 67080240)

1/3



Description

Conduit outlet is a Rejiband® accessory used to protect the wiring output to rigid or flexible conduits. Maximum diameter DN20 mm, With BK8 protection system. It allows connection of fittings in types PG13, PG16, PG21, M20 and M25. It is installed using the quick-fit Click system without the need of screws and can be placed in the flange or in the base of the tray. Suitable for all sizes of Rejiband® trays and available in various Protection Systems.

Advantages

It accepts fittings in sizes of: PG13, PG16, PG21, M20 and M25.

Fixing by quick mount click system.

Protects the cable outlet.

Quick installation without the need for screws or fastenings.

Can be used with TFA, ECOFLEX, TM-PVC + Pemsa RGp.

Applications

Allows the connection of fittings or glands and allows the output of electrical or telecommunications wiring from rigid or flexible conduits.

Solutions



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



u	10
---	----

Material	Steel with surface coating
-----------------	----------------------------

Working temperature range (°C)	-50 / 150 °C
---------------------------------------	--------------

Fire resistance	A1 No combustible
------------------------	-------------------

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic



Product applications

