3C Strut System

3C Strut Cantilever

Description

Base Support for 3C Strut with 3 sides that connect in a variety of ways to the perforations on the three sides of the Channels. Facilitates the fixixing and base support of the 3C Strut. Made of steel, available in various protection systems.

Advantages

Available in lengths 100, 150, 200, 300 y 400 mm.

It acts as a support as a horizontal support in cable tray installations.

Quick installation system. Thanks to the 3 side perforations allow a fast connection and screwing on the 3C Strut Cantilever using M8x65 hexagonal screw.

CE conformity in accordance to the low voltage directive 2014 /35 /UE and the international product standard IEC 61537

Available in PG and GC Protection Systems

Applications

Support for Cable Trays (rejiband®, pemsaband®, megaband®, among others) in ceiling installations in tunnels, service galleries, buildings or installations in industrial environments.

Solutions

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

3C Strut Cantilever

Main technical characteristics

100, 150, 200, 300, 400	2	Steel with surface coating	-50 / 150 °C	A1 No combustible	ETIM 10 EC001003

Product data

Ⓢ	Class IEC 61537		REF	kg/u
PG	Class 3	100	82003152	0,155
PG	Class 3	150	82003154	0,209
PG	Class 3	200	82003155	0,264
PG	Class 3	300	82003156	0,373
PG	Class 3	400	82003157	0,482
GC	Class 6	100	82003158	0,171
GC	Class 6	150	82003160	0,232
GC	Class 6	200	82003161	0,292
GC	Class 6	300	82003162	0,412
GC	Class 6	400	82003163	0,536

Ⓢ Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Ⓜ Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."