3C Strut System

3C Mounting Plate

Description

Fixing support for the connection of the 3C Strut to the ceiling, allowing them to have a variable angle that can adapt to tunnel vaults or inclined ceilings. Made from steel, available in various protection systems.

Advantages

Its design allows the creation of variable angles, adapting to arches of tunnels, galleries, and sloping walls.

Fixing piece by means of M8x65 screws for the installations of cable trays made up of 3-sided channels.

CE conformity in accordance to the low voltage directive 2014 /35 /UE and the international product standard IEC 61537

Available in PG and GC Protection Systems

Applications

Support for Cable Trays (rejiband®, pemsaband®, megaband®, among others) in ceiling installations in tunnels, service galleries, buildings or installations in industrial environments.

Solutions

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

3C Mounting Plate

Main technical characteristics

2	Steel with surface coating	-50 / 150 °C	A1 No combustible	ETIM 10 EC000896

Product data

Ⓢ	Class IEC 61537	REF	kg/u
PG	Class 3	82003172	0,188
GC	Class 6	82003175	0,209

Ⓢ Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Ⓜ Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."