
Wall Brackets

17/11/2026

Medium Duty Cantilever M-Plus (Ref: 82003773)



Description

Multipurpose cantilever for fixing Rejiband®, Pemsaband® and Megaband® cable trays in wall mounting, wall mounting on rail, or in ceiling mounting installed through reinforced cantilever arms. Width 500 mm, With PG protection system, PG3 finish

Advantages

In accordance with the IEC 61537 and CE standard with respect to directive 2014/35 / EU.

Available in PG, Pre-galvanized and AZ+, High-resistance alloy corrosion protection systems.

Universal mounting system compatible with Rejiband® wire mesh trays, Pemsaband® sheet trays and Megaband® ladder. A single support for all trays and ladder. Reduction in the number of references.

Applications

Suitable for Spiderband® cable suspension installations, for Rejiband® wire mesh trays, Pemsaband® sheet trays and other items such as luminaires, pipes, air conditioning, signage, etc. Recommended for indoor installations.

Solutions

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

Wall Brackets

17/11/2026

Medium Duty Cantilever M-Plus (Ref: 82003773)

Product data

ETIM 10	EC001003	**u**	1
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		**Material**	Steel with surface coating
Protection System	PG	**Working temperature range (°C)**	-50 / 150 ºC
Finish	PG3, Pregalvanised	**Fire resistance**	A1 No combustible
Resistance Class	Class 3		
Width (mm)	500		
kg/u	0,671		

Ⓢ Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Ⓜ Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."