

Medium Duty Cantilever M-Plus (Ref: 82003779)

1/2



Description

Multipurpose cantilever for fixing Rejiband®, Pemsaband® and Megaband® cable trays in wall mounting, wall mounting on rail, or in ceiling mounting installed through reinforced cantilever arms. Width 400 mm, With AZ+ protection system, ZM finish

Advantages

In accordance with the IEC 61537 and CE standard with respect to directive 2014/35 / EU.

Available in PG, Pre-galvanized and AZ+, High-resistance alloy corrosion protection systems.

Universal mounting system compatible with Rejiband® wire mesh trays, Pemsaband® sheet trays and Megaband® ladder. A single support for all trays and ladder. Reduction in the number of references.

Applications

Suitable for Spiderband® cable suspension installations, for Rejiband® wire mesh trays, Pemsaband® sheet trays and other items such as luminaires, pipes, air conditioning, signage, etc. Recommended for indoor installations.

Solutions



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



Product data			
ETIM 10		EC001003	
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		1,777	
Protection System		AZ+	
Finish		ZM High Resistance Alloy	
Resistance Class		Class 8	
Width (mm)		400	
kg/u		0,550	
u		1	
Material		Steel with surface coating	
Working temperature range (°C)		-50 / 150 °C	
Fire resistance		A1 No combustible	

Ⓢ Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

Ⓜ Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester
TPV - Thermoplastic