


Omega SPLUS Bracket (Ref: 62081304)

1/13



Description

Omega profile pendulum with safety plugs for the ceiling mounting of Rejiband® trays with click system and Pemsaband® trays with fixings. Width 300 mm, With BK8 protection system, BLACK C8 finish. Ceiling fixing system that allows you to configure different structures individually or with the help of omega SPLUS supports. Available in lengths of 300, 400, 500 and 600 mm. Made of steel in various Protection Systems.

Advantages

Available in several protection systems: PG, GC, BK8 and stainless steel AISI 304 and AISI 316L.

It includes plugs and protectors for ease of installation and to protect the installer.

N Mark of Aenor, in accordance with IEC 61537 and CE conformity to Directive 2014/35 / EU. Fire resistance E90 according to DIN 4102-12.

Reinforced omega profile. Increases the performance of the support.

Multipurpose system of fixing to the ceiling that allows various configurations for constructing structures individually or with the use of omega SPLUS supports.

Applications

Suitable for supporting medium loads of cable trays to the ceiling for electrical installations and / or of telecommunications in: Civil works, tunnels, car parks, public buildings, commercial centres, large infrastructures such as: Airports, underground, rail, tertiary sector, industrial naval, petrochemical, textile, chemical and food applications, according to the finish.

Solutions



RENEWABLE ENERGIES DATA CENTERS SERVICE AND RETAIL FIRE RESISTANCE SOLUTION



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."





Product data			
ETIM 10		EC000022	
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		1,303	
Protection System		BK8	
Finish		BLACK C8	
Resistance Class		Class 8	
Width (mm)		300	
kg/u		0,517	
u		5	
Material		Steel with surface coating	
SWL (kg)		38	
Working temperature range (°C)		-50 / 150 °C	
Fire resistance		E90 (90 min. 1000°C)	

Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester
TPV - Thermoplastic

Load diagrams

↓CTA↓ (kg)		kg
	100	60
	150	60
	200	60
	300	38
	400	28

↓CTA↓ (kg)		kg
	100	60
	150	60
	200	60
	300	38
	400	28

Product applications



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



