

Cantilever Arm Brace**Description**

Reinforcement accessory for 41 cantilever arm that acts as support and allows you to achieve a more resistant support system. Made from steel, available in various protection systems.

Advantages

It allows to achieve a more reinforced support system.

Fixing with M6, M8 and M10 screws.

Load values according to international standard IEC 61537.

Available in GC Protection Systems and INOX, Stainless steel AISI 316L

CE conformity in accordance to the low voltage directive 2014 /35 /UE.

Applications

Application as a horizontal wall support. For supporting Cable Trays (rejiband®, pemsaband®, megaband®, among others) but it is also very useful for supporting electrical conduits and other heating pipe installations, A/C, fire systems etc.

Solutions

Main technical characteristics

 5	 -25 / 105 °C	 A1 No combustible	ETIM 10 EC001003
--	--	---	---------------------

Product data

	 61537	Ref	kg/u	
GC	Class 6	82002627	1,744	Steel with surface coating
INOX	Class 9D	82002628	1,714	Acero inoxidable AISI 316L

 Protection System

- CU** - Copper electroplated
- PG** - Pregalvanised
- EZ** - Electrogalvanised
- BC** - Electrogalvanised Bichromate
- BK8** - High Resistance Coating
- GC** - Hot Dip Galvanising
- INOX** - Stainless Steel
- PT** - Polyester Paint
- AL** - Aluminum
- LN** - Brass or Nickel-plated brass

 Insulating materials

- PC+ABS** - Halogen Free Polycarbonate + ABS
- PVC** - Polyvinyl Chloride
- PP** - Halogen Free Polypropylene
- PA6** - Halogen Free Polyamide 6
- PA12** - Halogen Free Polyamide 12
- PU** - Polyurethane
- PE** - Polyethylene
- NBR** - NBR rubber
- PET** - Thermoplastic Polyester
- TPV** - Thermoplastic