



Description

Reinforcement accessory for 41 cantilever arm that acts as support and allows you to achieve a more resistant support system. Made from steel, available in various protection systems.

Advantages

Available in GC Protection Systems and INOX, Stainless steel AISI 316L

Fixing with M6, M8 and M10 screws.

It allows to achieve a more reinforced support system.

Load values according to international standard IEC 61537.

Applications

Application as a horizontal wall support. For supporting Cable Trays (rejiband®, pemsaband®, megaband®, among others) but it is also very useful for supporting electrical conduits and other heating pipe installations, A/C, fire systems etc.

Solutions



Product data

ETIM 10	EC001003	u	5
Huella de CO2. GWP A1-A3 (kg CO2 eq.)	4,517	Material	Steel with surface coating
Protection System	GC	Working temperature range (°C)	-25 / 105 °C
Finish	HDG, Hot Dip Galvanised	Fire resistance	A1 No combustible
Resistance Class	Class 6		
kg/u	1,744		

Protection System

- CU** - Copper electroplated
- PG** - Pregalvanised
- EZ** - Electrogalvanised
- BC** - Electrogalvanised Bichromate
- BK8** - High Resistance Coating
- GC** - Hot Dip Galvanising
- INOX** - Stainless Steel
- PT** - Polyester Paint
- AL** - Aluminum
- LN** - Brass or Nickel-plated brass

Insulating materials

- PC+ABS** - Halogen Free Polycarbonate + ABS
- PVC** - Polyvinyl Chloride
- PP** - Halogen Free Polypropylene
- PA6** - Halogen Free Polyamide 6
- PA12** - Halogen Free Polyamide 12
- PU** - Polyurethane
- PE** - Polyethylene
- NBR** - NBR rubber
- PET** - Thermoplastic Polyester
- TPV** - Thermoplastic

Product applications



