



Description

Reinforcement accessory for 41 cantilever arm that acts as support and allows you to achieve a more resistant support system. Made from steel, available in various protection systems.

Advantages

Available in GC Protection Systems and INOX, Stainless steel AISI 316L

Fixing with M6, M8 and M10 screws.

It allows to achieve a more reinforced support system.

Load values according to international standard IEC 61537.

Applications

Application as a horizontal wall support. For supporting Cable Trays (rejiband®, pemsaband®, megaband®, among others) but it is also very useful for supporting electrical conduits and other heating pipe installations, A/C, fire systems etc.

Solutions



Product data

ETIM 10	EC001003	u	5
Huella de CO2. GWP A1-A3 (kg CO2 eq.)	9,101	Material	Acero inoxidable AISI 316L
Protection System	INOX	Working temperature range (°C)	-25 / 105 °C
Finish	Stainless Steel AISI 316L	Fire resistance	A1 No combustible
Resistance Class	Class 9D		
kg/u	1,714		

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic



Product applications



