



Description

Cable suspension system for Pemsaband® sheet tray and other items such as luminaires, air conditioning, signalling, etc. For the suspension of sheet tray with Spiderband® it is fixed through the holes of the sidewall by means of a locking system, without the need for screws. Maximum admissible load of 35 kg. Made of steel, with EZ Protection System and available in lengths of 300, 460 and 500 mm.

Advantages

PG protection system (standard EN-ISO 2081), silver colour, suitable for indoor installations. Corrosion resistance class 3.

Suitable for the support of cable trays or other items with loads not exceeding 35 kg.

CE conformity to directive 2014/35 / EU.

Optimised design for quick and easy use. Installation savings in both material and labour.

It has a loop on the end for the connection of the steel cable.

Applications

Suitable for support by cable suspension of Pemsaband® sheet trays, as well as other items (luminaires, air conditioning, signage, etc.). Recommended for indoor installations.

Solutions



Product data						
Protection System		EZ	Material		Steel with surface coating	
Finish		EZ2, Electrogalvanised		SWL (kg)		35
L (mm)		550		Working temperature range (°C)		-50 / 150 °C
kg/u		0.031		Fire resistance		Flame retardant
u		10				

🔒 Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

🔌 Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic