



Description

Metal cover for the protection of cables in the Click Tee. Width 400 mm, With AZ+ protection system, ZM finish. It has a press-fit assembly system. Made of steel and available in various sizes and Protection Systems.

Advantages

The ends have an overlap to improve the fit with straight lids.

Available in all sizes and protection systems: PG, GC and stainless steel AISI304 and AISI316.

Press-fit click system requiring no additional parts.

Applications

It is used for the protection of wiring in the installation of Pemsaband® One perforated and solid tray installations where the Click Tee is used for installations in public buildings, infrastructures and civil works, tertiary sector and industrial applications.

Solutions



| Product data | | | |
|-------------------|--------------------------|--------------------------------|----------------------------|
| Protection System | AZ+ | kg/u | 1.980 |
| Finish | ZM High Resistance Alloy | u | 1 |
| Resistance Class | Class 8 | Material | Steel with surface coating |
| Width (mm) | 400 | Working temperature range (°C) | -50 / 150 °C |
| R stat. (mm) | 100 | Fire resistance | A1 No combustible |

| Protection System |
|-----------------------------------|
| CU - Copper electroplated |
| PG - Pregalvanised |
| EZ - Electrogalvanised |
| BC - Electrogalvanised Bichromate |
| BK8 - High Resistance Coating |
| GC - Hot Dip Galvanising |
| INOX - Stainless Steel |
| PT - Polyester Paint |
| AL - Aluminum |
| LN - Brass or Nickel-plated brass |

| Insulating materials |
|---|
| PC+ABS - Halogen Free Polycarbonate + ABS |
| PVC - Polyvinyl Chloride |
| PP - Halogen Free Polypropylene |
| PA6 - Halogen Free Polyamide 6 |
| PA12 - Halogen Free Polyamide 12 |
| PU - Polyurethane |
| PE - Polyethylene |
| NBR - NBR rubber |
| PET - Thermoplastic Polyester |
| TPV - Thermoplastic |