



Description

RP bush made of grey coloured polyethylene (RAL 7035) for protection of the ends of flexible conduits. Available in several sizes.

Advantages

CE conformity to the 2014/35 directive and the IEC 61386 standard.

Made from polypropylene, halogen free.

It protects the end of metal conduits to avoid any damage in the exit of the cables.

Applications

Suitable for placing on the ends of the TFA, TM, TM-PVC and Ecoflex® conduits for the protection of wiring and conductors in electrical installations of machines, tools, industrial equipment, robots, vehicles and special installations.

Solutions



Product data

Colour	Grey RAL 7035	u	100
DN	NW11	Material	Polypropylene
Ø d1 (mm)	12.1	IP	IP54
Ø d2 (mm)	21.9	Working temperature range (°C)	-25 / 90 °C
L (mm)	19.1	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA
kg/u	0.002		

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

