



### Description

RP bush made of grey coloured polyethylene (RAL 7035) for protection of the ends of flexible conduits. Available in several sizes.

### Advantages

CE conformity to the 2014/35 directive and the IEC 61386 standard.

Made from polypropylene, halogen free.

It protects the end of metal conduits to avoid any damage in the exit of the cables.

### Applications

Suitable for placing on the ends of the TFA, TM, TM-PVC and Ecoflex® conduits for the protection of wiring and conductors in electrical installations of machines, tools, industrial equipment, robots, vehicles and special installations.

### Solutions



Product data

Colour	Grey RAL 7035	u	20
DN	NW29	Material	Polypropylene
Ø d1 (mm)	26.7	IP	IP54
Ø d2 (mm)	42.2	Working temperature range (°C)	-25 / 90 °C
L (mm)	25.3	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA
kg/u	0.007		

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic

