
Flexible Conduits Connectors 27/04/2024

RGp Swivel Connector (Ref: 35012630)











1/2



Description

Straight swivel connector made of polyamide 6 in grey colour with metric thread for the installation of TFA, Ecoflex® and TM-PVC conduits. Plug-in connection system and threaded on the other end. Body and nut in grey colour (RAL 7035).

Advantages

High aesthetic component. RAL 7035 grey same as the other conduits or electrical materials. Also available in dark grey RAL 7001.

CE conformity to the 2014/35 directive and the IEC 61386 standard.

Manufactured in polyamide 6. Self-extinguishing, halogen-free according to UNE/EN 60754-2 y UNE/EN 60754-1 and flame-retardant.

Easy installation of fitting to a box thanks to its rotating body.

Protection index EN 60529: IP65.

Applications

Suitable for the connection of TFA, TM-PVC and Ecoflex® flexible conduits, in the conduction of electrical cables for building and industrial applications.

Solutions









Flexible Conduits Connectors 27/04/2024

RGp Swivel Connector (Ref: 35012630)

2/2

Product data			
Colour	Grey RAL 7035	kg/u	0.084
DN	NW48	u	5
M/PG	M63	Material	Poyamide 6
G (mm)	15	IP	IP65
L (mm)	76	Working temperature range (°C)	-25 / 105 °C
Torque wrench	69	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR

S Protection System

- CU Copper electroplated
- PG Pregalvanised
- EZ Electrogalvanised
- BC Electrogalvanised Bichromate
- **BK8** High Resistance Coating
- GC Hot Dip Galvanising
- INOX Stainless Steel
- PT Polyester Paint
- AL Aluminum
- LN Brass or Nickel-plated brass

™ Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

- PVC Polyvinyl Chloride
- PP Halogen Free Polypropylene
- PA6 Halogen Free Polyamide 6
- PA12 Halogen Free Polyamide 12
- **PU** Polyurethane
- PE Polyethylene
- NBR NBR rubber
- PET Thermoplastic Polyester
- TPV Thermoplastic





DE LA LLAMA







