
GC Rigid Conduit Accessories

RGC Stand off Clamp

25/04/2024













Description

GC Protection System carbon steel stand off clamp available in several diameters for fixing rigid metal conduits. Fixing with screws. it has a foot that allows separation of the conduit from the floor or wall.

Advantages

Available in various sizes: NW16, NW20, NW25, NW32, NW40, NW50 and NW63.

It has a foot that allows the conduit to stand off from the floor or wall.

Working temperature: -45°C to + 400°C.

CE conformity to the 2014/35 directive and the IEC 61386 standard.

Manufactured in GC protection system steel (standard EN ISO 1461), suitable for outdoor installations and in aggressive environments. Grade 4 corrosion resistance, according to IEC 61386. High indoor and outdoor protection.

Applications

Suitable for fixing RLGC and RRGC hot dip galvanised rigid metal conduits in installations that require high mechanical performance and high resistance to corrosion. For building applications. Tertiary and industrial sectors with high security requirements. Premises of public attendance or with risk of fire or explosion. Installation in outdoor and aggressive environments.

Solutions













GC Rigid Conduit Accessories 25/04/2024

RGC Stand off Clamp

2/2

Main technical characteristics

(S) GC

F HDG, Hot Dip Galvanised

DN NW16, NW20, NW25, NW32, NW40, NW50, NW63

***** -45 / 400 °C

🙎 LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA

ETIM EC000464

Product data

DN	ReF	kg/u	A
NW16	55033116	0.030	50
NW20	55033120	0.034	50
NW25	55033125	0.043	50
NW32	55033132	0.048	25
NW40	55033140	0.055	25
NW50	55033150	0.067	25
NW63	55033163	0.080	20

S Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

[®] Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic











