




Description

Zinc plated steel clamp with elastomer profile for fixing Macroflex® NW70 and NW95 conduits that protects it from vibrations.

Advantages

CE conformity to the 2014/35 directive and the IEC 61386 standard.

Available in various sizes.

Manufactured in PG protection system steel with a NBR elastomer profile.

Protect from vibrations.

Working temperature: -25°C to + 90°C.

Applications

Suitable for fixing large diameter Pemsaflex® and Macroflex® conduits for the protection of wiring and conductors in electrical installations of machines, tools, industrial equipment, robots, vehicles and special installations.

Solutions



Product data

ETIM 10	EC000127	H (mm)	132
Huella de CO2. GWP A1-A3 (kg CO2 eq.)		kg/u	0,075
Protection System	EZ	u	10
Finish	EZ2, Electrogalvanised	Material	ACERO CON PROT. SUPERFICIAL,NBR
DN	NW95	Working temperature range (°C)	-15 / 120 °C
L (mm)	150	Fire resistance	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA
A (mm)	25		
Ø C (mm)	8.3		

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."