

EMC Nut



Description

Advantages

Applications

Solutions



Main technical characteristics

LTN	PG 7, PG 9, PG11, PG13, PG16, PG21, PG29, PG36, PG42, PG48, M12, M16, M20, M25, M32, M40, M50, M63	Nickel-plated brass
-60 / 200 °C	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA	ETIM 10 EC000940

Product data

			Ref	kg/u	
PG 7	3.3	15	40016007	0,002	100
PG 9	3.3	18	40016009	0,002	50
PG11	3.5	21	40016011	0,003	50
PG13	3.5	23	40016013	0,003	50
PG16	3.5	26	40016016	0,004	50
PG21	4	32	40016021	0,008	25
PG29	4.6	40	40016029	0,010	20
PG36	5.6	50	40016036	0,017	10
PG42	5.6	60	40016042	0,033	5
PG48	6.1	65	40016048	0,036	5
M12	3.3	15	40017120	0,003	100
M16	3.5	19	40017160	0,004	50
M20	3.5	24	40017200	0,005	50
M25	3.5	30	40017250	0,009	25
M32	4	36	40017320	0,011	20
M40	4.6	45	40017400	0,017	10
M50	5.6	55	40017500	0,028	5
M63	6.7	70	40017630	0,038	5

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene

EMC Nut

- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic

