
TCM Nut





Description

Nickel-plated brass nut with metric or PG thread for connecting conduits, connectors and metal cable glands.

Advantages

Compatible with metric or PG metal threaded cable glands for all ranges of rigid and flexible conduits.

Working temperature: -45°C to + 150°C.

CE conformity to the 2014/35 directive and the IEC 61386 standard.

Made of nickel-plated brass.

Applications

Suitable for connection of threaded fittings of all ranges of rigid, flexible and metal conduits and metal cable glands for the management of electrical cables in building and industrial applications.

Solutions

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

Main technical characteristics

Ⓢ LTN | Ⓕ Nickel-plated brass | PG 7, PG 9, PG11, PG13, PG16, PG21, PG29, PG36, PG42, PG48, M12, M16, M20, M25, M32, M40, M50, M63

Ⓜ Nickel-plated brass | -45 / 150 °C | LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA | ETIM EC000129

Product data

			REF	kg/u	
PG 7	2.8	15	40010007	0.002	100
PG 9	2.8	18	40010009	0.002	100
PG11	3	21	40010011	0.003	100
PG13	3	23	40010013	0.003	100
PG16	3	26	40010016	0.005	100
PG21	3.5	32	40010021	0.007	100
PG29	4	41	40010029	0.012	50
PG36	5	51	40010036	0.019	25
PG42	5	60	40010042	0.029	25
PG48	5.5	64	40010048	0.030	25
M12	2.8	15	40011120	0.002	100
M16	2.8	19	40011160	0.003	100
M20	3	24	40011200	0.004	100
M25	3.5	30	40011250	0.007	100
M32	4	36	40011320	0.010	50
M40	5	46	40011400	0.020	25
M50	5	60	40011500	0.028	25
M63	6	70	40011630	0.046	25

Ⓢ Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Ⓜ Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

TCM Nut

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."