



Description

Halogen-free aluminium clip for the fixing of RAL conduits in installations that require an excellent degree of resistance to corrosion and high mechanical performance. Accessory for mounting rigid conduits with fixing by pressure. Available for various conduit sizes.

Advantages

Accessory for the assembly of rigid pipes with fixing of the tube by means of pressure. Lightweight and easy to install.

Available in various sizes: NW16, NW20, NW25, NW32 and NW40.

Working temperature: -45°C to + 250°C.

CE conformity to the 2014/35 directive and the EN IEC 61386 standard.

Made of aluminum, suitable for installations in industrial plants and aggressive environments. Grade 4 corrosion resistance, according to IEC 61386. High indoor and outdoor protection.

Applications

It is recommended for RAL aluminium conduits in installations that require high mechanical performance. With a high resistance to corrosion in applications of industrial plants, tertiary and industrial sector with high safety requirements. Premises with risk of fire or explosion. Installation outside and in aggressive environments.

Solutions



Main technical characteristics

AL	NW16, NW20, NW25, NW32, NW40	Aluminum	-45 / 250 °C
LIBRE DE HALÓGENOS, NO PROPAGADOR DE LA LLAMA		ETIM 10 EC000368	

Product data

DN	Ref	kg/u	
NW16	55022016	0,009	50
NW20	55022020	0,011	50
NW25	55022025	0,013	50
NW32	55022032	0,017	50
NW40	55022040	0,026	25

Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

