



Description

Threaded Tee with removable cover for the connection of RR conduits in installations requiring high mechanical performance and an average resistance to corrosion. With an IP54 protection index. Accessory to create a branch in the conduit run. Made of aluminium and available in different diameters.

Advantages

Threaded connection system. Accessory to create branches in the routing of cable conduits.

Protection index EN 60529: IP54.

CE conformity to the 2014/35 directive and the IEC 61386 standard.

Made of cast aluminum. Grade 4 corrosion resistance, according to IEC 61386. High indoor and outdoor protection.

Applications

Suitable for the connection of RR metal rigid conduits in building, tertiary and industrial applications with high safety requirements. Premises of public attendance and premises with risk of fire or explosion.

Solutions



Main technical characteristics

AL	ALU, Aluminium	DN NW16, NW20, NW25, NW32, NW40, NW50	M16, M20, M25, M32, M40, M50	Aluminum
IP54	-45 / 400 °C	LIBRE DE HALÓGENOS,NO PROPAGADOR DE LA LLAMA	ETIM EC002922	

Product data

DN			L _(mm)	A _(mm)	B _(mm)	Ref	kg/u	
NW16	M16	20	96	61	30.5	55080016	0.136	10
NW20	M20	21.5	96	61	30.5	55080020	0.121	10
NW25	M25	26.5	111	71	35.5	55080025	0.233	8
NW32	M32	32	146	96	51.5	55080032	0.469	2
NW40	M40	33.5	146	96	51.5	55080040	0.734	2
NW50	M50	43.5	183	120	61.5	55080050	1.252	1

Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic