
1/2

Cable Tray Accessories 03/05/2024

Tee Click (Ref: 70062260)

















Description

Metal accessory for the construction of a Tee at any point in the Pemsaband® and Inducanal® trays. Of 60 mm height, Width 600 mm, With INOX protection system, I316L finish. The Pemsaband® Tee is used to create a T-shaped junction, transforming a cable distribution line into two separate paths. Quick connection assembly using the Click system without couplers. Made of steel in various sizes and Protection Systems.

Advantages

Side flanges have the same profile as the straight section of the trays thus forming a continual view of the installation.

It has pre-formed holes in the sides to allow for the connection of fittings and conduits for the exit of cables.

Available in all sizes and protection systems: PG, GC and stainless steel AISI304 and AISI316.

The PG protection system is supplied flat for later assembly and provides savings on transportation and storage by reducing its volume.

Assembly by means of the quick-connect click system without the need for couplers. Patented Universal System that has holes compatible with the connection to other sheet metal tray.

Applications

Used for the creation of tees in the Pemsaband® and Inducanal® ranges for the Support, management and distribution of Electrical and/or telecommunications cables in public buildings, infrastructures and civil works, tertiary sector and industrial applications.

Solutions











Cable Tray Accessories 03/05/2024

Tee Click (Ref: 70062260)

2/2

P	ro	dι	ıct	d	a	ta
-	·	uu	ıcı	u	a	LC

Protection System	INOX	u	1	
Finish	Stainless Steel AISI 316L	Material	Acero inoxidable AISI 316L	
Resistance Class	Class 9D	Impact Strength (J)	20 J	
Flange (mm)	60	IP	IP44	
Width (mm)	600	Working temperature range (°C)	-50 / 150 °C	
R stat. (mm)	100	Fire resistance	A1 No combustible	
kg/u	3.670			

S Protection System

- CU Copper electroplated
- PG Pregalvanised
- **EZ** Electrogalvanised
- BC Electrogalvanised Bichromate
- **BK8** High Resistance Coating
- GC Hot Dip Galvanising
- INOX Stainless Steel
- PT Polyester Paint
- AL Aluminum
- LN Brass or Nickel-plated brass

M Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

- PVC Polyvinyl Chloride
- PP Halogen Free Polypropylene
- PA6 Halogen Free Polyamide 6
- PA12 Halogen Free Polyamide 12
- PU Polyurethane
- PE Polyethylene
- NBR NBR rubber
- PET Thermoplastic Polyester
- TPV Thermoplastic









