Fixings

23/11/2026



# Hexagonal Nut ( Ref: 67020095 )



## Description

Hexagonal metal nut that together with a bolt enables the fixing of joints, supports and channel structures for installations of trays, joints, flanges for supports and accessories. M 8, M 8, With EZ protection system, EZ3 finish. Available in M8 and M10. Made of steel and in various Protection Systems.

## Advantages

CE conformity to directive 2014/35 / EU.

Available in several protection systems: EZ, GC and AISI316L stainless steel.

Very versatile piece for use in any joint along with a M8 or M10 hexagonal set screw.

## Applications

Suitable for the fixing of joints, supports and channel structures in tray installations for the management of electrical cables and / or telecommunications in public buildings, infrastructures and civil works, industrial facilities and the tertiary sector.

## Solutions



Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

# Hexagonal Nut ( Ref: 67020095 )

## Product data

| | | | |
|---|---|---|---|
| **ETIM 10** | EC003863 | **u** | 100 |
| **Huella de CO2. GWP A1-A3 (kg CO2 eq.)** | | **Material** | Steel with surface coating |
| **Protection System** | EZ | **Working temperature range (°C)** | -50 / 150 °C |
| **Finish** | EZ3, Electrogalvanised | **Fire resistance** | A1 No combustible |
| **Resistance Class** | Class 3 | | |
| **M/PG** | M 8 | | |
| **kg/u** | 0,005 | | |

## Ⓢ Protection System

**CU** - Copper electroplated

**PG** - Pregalvanised

**EZ** - Electrogalvanised

**BC** - Electrogalvanised Bichromate

**BK8** - High Resistance Coating

**GC** - Hot Dip Galvanising

**INOX** - Stainless Steel

**PT** - Polyester Paint

**AL** - Aluminum

**LN** - Brass or Nickel-plated brass

## Ⓜ Insulating materials

**PC+ABS** - Halogen Free Polycarbonate + ABS

**PVC** - Polyvinyl Chloride

**PP** - Halogen Free Polypropylene

**PA6** - Halogen Free Polyamide 6

**PA12** - Halogen Free Polyamide 12

**PU** - Polyurethane

**PE** - Polyethylene

**NBR** - NBR rubber

**PET** - Thermoplastic Polyester

**TPV** - Thermoplastic



Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."