



Description

Metal nut for inserting in the rung of the Megaband® ladder to enable the connection of any component or device. M 8, M 8, With GC protection system

Advantages

Suitable for the connection of any item or device in the installation of Megaband® ladder.

Available in two sizes: M6 and M8.

Available in several protection systems: EZ, GC and AISI316L stainless steel.

Applications

Used for the connection of any item or device to the rung of the Megaband® ladders management and distribution of cables in electrical and telecommunications installations in public buildings, infrastructures and civil works, industrial facilities, tertiary sector.

Solutions



ETIM 10

EC000096

Huella de CO2. GWP A1-A3 (kg CO2 eq.)

Protection System

GC

Finish

Zinc Nickel

Resistance Class

Class 8

M/PG

M 8

kg/u

0,013

u

100

Material

Steel with surface coating

Working temperature range (°C)

-50 / 150 °C

Fire resistance

A1 No combustible

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Reijband, Pemsaband, Inducanal, Rejtech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."