



Description

Component for joining sections of trays using the Click system. It is suitable for all widths of Rejiband trays of heights 35, 60 and 100 mm, with surface protection. It is assembled without the need for any special tools and allows the joining between sections of Rejiband trays in less time, ensuring the mechanical strength of the joint and electrical continuity, according to IEC61537 standard. Made of steel and available in various Protection Systems.

Advantages

It is installed on the tray without screws.

Simple and quick assembly without the need of special tools.

Electrical continuity guaranteed according to standard IEC61537.

Available in various protection systems: EZ, BC, GC or high resistance BK8, depending on the type of application.

Applications

Suitable for the fast connection of Rejiband trays in electrical and/or telecommunications installations in: Civil works, Tunnels, Car Parks, Public Buildings, Shopping Centres, Large Infrastructures, Airports, Metro Lines, Railway. Tertiary Sector and industrial applications: Naval, Petrochemical, Textile, Chemical, Food.

Solutions



www.pemsa-rejiband.com



Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

Main technical characteristics

 25	 Steel with surface coating	 -50 / 150 °C	 A1 No combustible	ETIM 10 EC002413
---	--	--	---	---------------------

Product data

		Ref	kg/u
EZ	Class 3	64010020	0,074
GC	Class 8	64030030	0,077
BK8	Class 8	64080030	0,075

 Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

 Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic

Product applications





