



### Description

Component for joining sections of trays using the Click system. With BC protection system, BYCRO finish. It is suitable for all widths of Rejiband trays of heights 35, 60 and 100 mm, with surface protection. It is assembled without the need for any special tools and allows the joining between sections of Rejiband trays in less time, ensuring the mechanical strength of the joint and electrical continuity, according to IEC61537 standard. Made of steel and available in various Protection Systems.

### Advantages

Available in various protection systems: EZ, BC, GC or high resistance BK8, depending on the type of application.

Electrical continuity guaranteed according to standard IEC61537.

Simple and quick assembly without the need of special tools.

It is installed on the tray without screws.

### Applications

Suitable for the fast connection of Rejiband trays in electrical and/or telecommunications installations in: Civil works, Tunnels, Car Parks, Public Buildings, Shopping Centres, Large Infrastructures, Airports, Metro Lines, Railway. Tertiary Sector and industrial applications: Naval, Petrochemical, Textile, Chemical, Food.

### Solutions



Product data			
Protection System	BC	u	25
Finish	BYCRO	Material	Steel with surface coating
Resistance Class	Class 5	Working temperature range (°C)	-50 / 150 °C
kg/u	0.074	Fire resistance	A1 No combustible

Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester
TPV - Thermoplastic

## Product applications





