



### Description

Coupling piece for joining straight sections and accessories of Megaband® ladder by using M8 hexagonal nuts and bolts. Of 100 mm height, With INOX protection system, I304 finish. Suitable for Megaband® ladder of 60,100, 120 and 150mm height, maintaining electrical continuity, according to IEC 61537. Made of steel, available in different Protection Systems.

### Advantages

Suitable for Megaband® ladder, heights 85, 100 and 120 mm.

Wide variety of sizes, protection systems and accessories to adapt to the requirements of each electrical installation.

Electrical continuity guaranteed according to standard IEC61537.

Very simple assembly by fixing the coupler to the Megaband® ladder by means of M8 hexagonal nuts and bolts.

Only necessary if straight sections are cut since the Megaband ladder has an integrated coupling system.

### Applications

Suitable for the joining of straight sections and accessories of the Megaband ladder for the management of cables in electrical and telecommunication installations in public buildings, infrastructures and civil works, industrial installations, tertiary sector.

### Solutions



## Product data

|                                              |                          |                                       |                          |
|----------------------------------------------|--------------------------|---------------------------------------|--------------------------|
| <b>ETIM 10</b>                               | EC002413                 | <b>u</b>                              | 20                       |
| <b>Huella de CO2. GWP A1-A3 (kg CO2 eq.)</b> | 0,596                    | <b>Material</b>                       | Stainless steel AISI 304 |
| <b>Protection System</b>                     | INOX                     | <b>Working temperature range (°C)</b> | -50 / 150 °C             |
| <b>Finish</b>                                | Stainless Steel AISI 304 | <b>Fire resistance</b>                | A1 No combustible        |
| <b>Resistance Class</b>                      | Class 9C                 |                                       |                          |
| <b>Flange (mm)</b>                           | 100                      |                                       |                          |
| <b>kg/u</b>                                  | 0,112                    |                                       |                          |

## 🔒 Protection System

**CU** - Copper electroplated

**PG** - Pregalvanised

**EZ** - Electrogalvanised

**BC** - Electrogalvanised Bichromate

**BK8** - High Resistance Coating

**GC** - Hot Dip Galvanising

**INOX** - Stainless Steel

**PT** - Polyester Paint

**AL** - Aluminum

**LN** - Brass or Nickel-plated brass

## 🧊 Insulating materials

**PC+ABS** - Halogen Free Polycarbonate + ABS

**PVC** - Polyvinyl Chloride

**PP** - Halogen Free Polypropylene

**PA6** - Halogen Free Polyamide 6

**PA12** - Halogen Free Polyamide 12

**PU** - Polyurethane

**PE** - Polyethylene

**NBR** - NBR rubber

**PET** - Thermoplastic Polyester

**TPV** - Thermoplastic



## Product applications





