



Description

Advantages

Applications

Solutions



www.pemsa-rejiband.com

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."



Main technical characteristics

 PG3, Pregalvanised, ZM High Resistance Alloy	 12, 25, 50	 Steel with surface coating	 -50 / 150 °C	 A1 No combustible
ETIM 10				

Product data

				Ref	kg/u
PG	PG3, Pregalvanised	Class 3	12	82004955	0,079
PG	PG3, Pregalvanised	Class 3	25	82004957	0,095
PG	PG3, Pregalvanised	Class 3	50	82004958	0,147
AZ+	ZM High Resistance Alloy	Class 8	25	82004961	0,095
AZ+	ZM High Resistance Alloy	Class 8	50	82004962	0,147

 Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

 Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic

