Threaded Rod





Description

Advantages

Applications

Solutions

FOOD INDUSTRY

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

Threaded Rod

Main technical characteristics

M 6, M 8, M10

-50 / 150 °C

ETIM 10
EC000028

Product data

Ⓢ	Class IEC 61537		L (mm)	REF	kg/u	u	Ⓜ	F kg	
EZ	Class 3	M 6	500	67010140	0,120	50	Steel with surface coating	195	A1 No combustible
EZ	Class 3	M 6	1000	67010141	0,240	50	Steel with surface coating	195	A1 No combustible
GC	Class 8	M 8	1000	67030045	0,320	50	Steel with surface coating	400	E90 (90 min. 1000°C)
INOX	Class 9D	M 8	500	67060044	0,160	50	Acero inoxidable AISI 316L	400	E90 (90 min. 1000°C)
INOX	Class 9D	M 8	1000	67060045	0,320	50	Acero inoxidable AISI 316L	400	E90 (90 min. 1000°C)
INOX	Class 9D	M 6	1000	67060141	0,240	50	Acero inoxidable AISI 316L	195	A1 No combustible
INOX	Class 9D	M10	1000	67060145	0,490	25	Acero inoxidable AISI 316L	500	E90 (90 min. 1000°C)
BK8	Class 8	M 8	1000	67080045	0,320	50	Steel with surface coating	400	E90 (90 min. 1000°C)
EZ	Class 3	M 8	500	81000440	0,160	50	Steel with surface coating	400	E90 (90 min. 1000°C)
EZ	Class 3	M 8	1000	81000441	0,320	50	Steel with surface coating	400	E90 (90 min. 1000°C)
EZ	Class 3	M10	1000	81000442	0,490	50	Steel with surface coating	500	E90 (90 min. 1000°C)

Ⓢ Protection System

CU - Copper electroplated

PG - Pregalvanised

EZ - Electrogalvanised

BC - Electrogalvanised Bichromate

BK8 - High Resistance Coating

GC - Hot Dip Galvanising

INOX - Stainless Steel

PT - Polyester Paint

AL - Aluminum

LN - Brass or Nickel-plated brass

Ⓜ Insulating materials

PC+ABS - Halogen Free Polycarbonate + ABS

PVC - Polyvinyl Chloride

PP - Halogen Free Polypropylene

PA6 - Halogen Free Polyamide 6

PA12 - Halogen Free Polyamide 12

PU - Polyurethane

PE - Polyethylene

NBR - NBR rubber

PET - Thermoplastic Polyester

TPV - Thermoplastic

Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

Threaded Rod

Load diagrams

Product applications



Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."

Threaded Rod



Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."