




QUICK-CONNECT PERFORATED METAL CABLE TRAY


pemsa**band**[®]
 **VULCAN**



Smarter, Stronger, Built To Last, Sustainable



www.pemsa.co.uk



pemsaband®
VULCAN

Quick-Connect perforated metal cable tray

Smarter


- Quick-connect system.
- Easy and practical to install.
- Hole pattern designed to facilitate cable fixing.



No tools



New Quick-fixing clip




Alternative coupling with screws.
67010093 / 67030093



Smarter

- Wide range of sizes. Light, Medium and Heavy Duty
- Wide range of accessories. Dividers, Covers, Bends, T-joints, Crossovers, Risers, etc
- Brackets and accessories for connecting lights or devices



Stronger




Safety working loads according to IEC 61537, edition 3.

Protection Systems against corrosion

Protection system	PG	AZ+
Finish	PG3	ZM
	Pregalvanised	Zinc Magnesium Alloy
Standard	BS-EN 10346	BS-EN 10346
Corrosion Class	3	8
Corrosivity Cat. ISO 9223	C3	C5



Consult online catalogue





Smarter



New design of profile and safety edge



+80%

The contact area increases by 80%

Protects cables and strengthens the cable tray.

Increases the contact surface between the cable tray and cover, ensuring electrical continuity in accordance with Edition 3 of the IEC 61357 standard.



Built to last



BS-EN 61537

Designed to meet the most rigorous requirements of the latest edition of the international standard for cable trays, IEC 61537, 3rd edition and BS EN 61537:2007



Designed to meet the requirements set out in BS 7671, Requirements for Electrical Installations, and the IET Wiring Regulations



Compliance with UKCA marking and the UK Electrical and Equipment (Safety) Regulations 2016 (S.I. 2016 No. 1101)



EU Declaration of Conformity in accordance with Directive 2014/35/EU

Sustainable Design



Developed in accordance with ISO 14001 standards



Assessed by ECOVADIS. Bronze Medal. We are in the top 35% of companies globally



A VERIFIED ENVIRONMENTAL DECLARATION



Life cycle analysis, carbon footprint and circularity data available. (EPD pending)




Manufactured from 100% recyclable steel



pemsa^{band}® VULcan

Quick-connect perforated metal cable tray



BS-EN 61537



Light Duty



12 • 50-300 • 3000

PG	PG	
50	82004621	8
75	82004622	8
100	82004623	8
150	82004624	4
225	82004625	4
300	82004626*	4

(*) The height of part number 82004626 is 18 mm

Medium Duty



25 • 50-900 • 3000

PG	PG	AZ+	
50	82004627	82004653	8
75	82004628	82004654	8
100	82004629	82004655	8
150	82004630	82004656	4
225	82004631	82004657	4
300	82004632	82004658	4
450	82004633	82004659	2
600	82004634	82004660	2
750	82004635*	82004661*	2
900	82004636*	82004662*	2

(*) The length of this sizes is 2 meters



Heavy Duty



50 • 50-900 • 3000

PG	PG	AZ+	
50	82004637	82004663	8
75	82004638	82004664	8
100	82004639	82004665	8
150	82004640	82004666	4
225	82004641	82004667	4
300	82004642	82004668	4
450	82004643	82004669	2
600	82004644	82004670	2
750	82004645*	82004671*	2
900	82004646*	82004672*	2

(*) The length of this sizes is 2 meters



(1*) Quick fitting clip



GC	GC	kg/m	
12	81000553	0.009	50

(2*) Straight coupler



PG	PG	AZ+	kg/m	
12	82004955*	-	0.079	10
25	82004957	82004961	0.095	10
50	82004958	82004962	0.147	10

(*) * Also compatible with 18 mm of height



Take a look at our wide range of products in stock:



rejiband®
RAPIDE

Quick connect basket tray



megaband®

Cable ladder



metatrays®

Insulating PVC Cable tray



support system

Wide Range of Brackets



Pemsa UK



1 Sussex Avenue
Leeds LS10 2LF
Tel.: +44 113 277 9090
sales@pemsa.co.uk
www.pemsa.co.uk



www.pemsa.co.uk



85000307. ED 0. September 2026